



**LAKE ELECTROFISHING DATA COLLECTION SHEET (FALL)**  
Form 3600A-191 8-95

Department of Natural Resources

Lake: Black Oak MWB Code: 1630100 Date: 10/06/08 County: Vilas Collector(s): Gilbert, Schinker, Hlaverson

Target Fish: Juvenile Gamefish Survey Type: CPE Mark Given: None Water Temperature: 62°F Station: Portion of Shoreline

Adverse Conditions: None Gear Type: Boomshocker Distance Shocked: 7.0 miles

Volts: 222 Amps: 1.7 Current Type: AC DC Pulsed DC Pulse Rate: None Duty Cycle: None

Shocking Start Time: 19:05 Shocking End Time: 21:20 Generator Start Hour: 0.0 Generator End Hour: 2.3

Number of Dippers:  1  2 Entire Shoreline Shocked:  Y  N  I Dipnet Mesh Size: 3/8 inch bar H2O Clarity: 6 feet

Walleye < 12.0"			
Inches	Number	Inches	Number
<3.0		7.5	
3.0		7.6	
3.1		7.7	
3.2		7.8	
3.3		7.9	
3.4		8.0	
3.5		8.1	
3.6		8.2	
3.7		8.3	
3.8		8.4	
3.9		8.5	
4.0		8.6	
4.1		8.7	
4.2		8.8	
4.3		8.9	
4.4		9.0	
4.5		9.1	
4.6		9.2	
4.7		9.3	
4.8		9.4	
4.9		9.5	
5.0		9.6	
5.1	1	9.7	
5.2		9.8	
5.3		9.9	1
5.4		10.0	
5.5	2	10.1	
5.6		10.2	
5.7		10.3	
5.8		10.4	
5.9	1	10.5	
6.0	1	10.6	
6.1	2	10.7	
6.2	1	10.8	
6.3		10.9	
6.4		11.0	
6.5	1	11.1	
6.6	2	11.2	
6.7	1	11.3	
6.8		11.4	
6.9	1	11.5	
7.0		11.6	
7.1		11.7	
7.2		11.8	
7.3		11.9	
7.4		Total:	14

Inches	Walleye	Northern Pike	Muskellunge	Largemouth Bass	Smallmouth Bass	Inches	Walleye	Northern Pike	Muskellunge
<1.5						24.5-24.9			
1.5-1.9						25.0-25.4			
2.0-2.4						25.5-25.9			
2.5-2.9						26.0-26.4			
3.0-3.4						26.5-26.9			
3.5-3.9						27.0-27.4			
4.0-4.4				1		27.5-27.9			
4.5-4.9						28.0-28.4			
5.0-5.4				1		28.5-28.9			
5.5-5.9					1	29.0-29.4			
6.0-6.4						29.5-29.9			
6.5-6.9					1	30.0-30.4			
7.0-7.4				1		30.5-30.9			
7.5-7.9						31.0-31.4			
8.0-8.4						31.5-31.9			
8.5-8.9				1		32.0-32.4			
9.0-9.4						32.5-32.9			
9.5-9.9						33.0-33.4			
10.0-10.4						33.5-33.9			
10.5-10.9		1				34.0-34.4			
11.0-11.4						34.5-34.9			
11.5-11.9						35.0-35.4			
12.0-12.4	1					35.5-35.9			
12.5-12.9						36.0-36.4			
13.0-13.4						36.5-36.9			
13.5-13.9						37.0-37.4			
14.0-14.4						37.5-37.9			
14.5-14.9						38.0-38.4			
15.0-15.4						38.5-38.9			
15.5-15.9						39.0-39.4			
16.0-16.4						39.5-39.9			
16.5-16.9						40.0-40.4			
17.0-17.4						40.5-40.9			
17.5-17.9						41.0-41.4			
18.0-18.4						41.5-41.9			
18.5-18.9						42.0-42.4			
19.0-19.4						42.5-42.9			
19.5-19.9						43.0-43.4			
20.0-20.4						43.5-43.9			
20.5-20.9						44.0-44.4			
21.0-21.4						44.5-44.9			
21.5-21.9						45.0-45.4			
22.0-22.4						45.5-45.9			
22.5-22.9						46.0-46.9			
23.0-23.4						47.0-47.9			
23.5-23.9						48.0-48.9			
24.0-24.4						49.0-49.9			
Totals:	1	1	0	4	2	50.0+			